

Production Description

Meiyuan T-F10003SP Aluminum Foil Tape is customized product for certain customer, which is 100 μ m nominal dead soft pure aluminum foil coated with 50micron acrylic pressure-sensitive adhesive and protected by single-sided PE coated silicone release liner.

Technical Data Sheet

Property	Unit	Value	Test Method
Total Thickness (without liner)	μ m	150	PSTC-33 / ASTM D3652
Peel Adhesion (180°)	N/25mm	≥ 18	PSTC-1 / ASTM D3330
Tack Rolling Ball	cm	≤ 20	PSTC-6 / ASTM D3121
Tensile Strength	N/25mm	≥ 162	PSTC-31 / ASTM D3759
Elongation	%	≥ 6	PSTC-31 / ASTM D3759
Application Temperature	°C	+10~ 40	-----
Heat Resistance	°C	-20~ 120	-----

Remarks:

1. The data above are typical results and subject to change without notice.
2. Tolerance: Weight and Thickness: $\pm 10\%$; Width: $\pm 3\text{mm}$; Length: Cut Roll: $\pm 0.3\text{m}$, Jumbo Roll $\pm 0.5\%$.
3. The product should be stored at room temperature and kept from wet and heat source.
Shelf life: One year from shipment date when stored at 21°C (70°F)/ 50% RH out of direct sunlight.
4. It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.
5. The user should take test and do trial-application on the above products before coming into application so as to witness and ensure suitability for user's special purpose and technique.

JIANGYIN MEIYUAN INDUSTRIES CORPORATION

Address: No.11 Songwentou Road, Yunting Industry Zone, Jiangyin City, Jiangsu Province, China
Postcode: 214400
Website: www.meiyuan.com